

AERO25

Standard **3 Ply Mask**

Complies with F2100 Level 1 standard

- ✓ **High Fluid Resistance**
- ✓ **Higher Breathability**
- ✓ **High Bacterial Filtration Efficiency**
- ✓ **Nose wire enabling comfort fit**
- ✓ **Soft inner lining material improves comfort**



Three-layer construction of Polypropylene, Meltblown and Polypropylene for excellent results

Test Standard	Test Description	ASTM set value	Unit	AERO25 Test Data
ASTM F 2101	Bacterial Filtration Efficiency (BFE) @ 3 micron	> 95	%	99.5
IS 16289:2014 Annex C	Breathability	<50	Pa/Cm2	19
ASTM F 2299/F2299M-03	Particulate Filtration Efficiency (PFE) @ 0.3 micron	> 95	%	96.73
16 CFR Part 1610	Flammability	Class 1		Class 1
ASTM F1862/1862M-13	Splash Resistance	160	mm Hg	160

Packing - 50/box. Follow proper disposal of masks after use.

Storage - 60 months in original packing.

Manufactured by:

Filtrowin Industries, Plot No. 41, CSEZ, Kakkanad, Kochi - 37, Kerala, India, Tel: +91 484 241 3021

Aerofil Filters India Pvt. Ltd., EP/II/433, Maranadu PO, Kollam - 691505, Kerala, India, T: +91 86061 98157

www.aerofil.de | E: info@aerofilinternational.com | International offices: •Germany •Portugal •UAE

A product from Aerofil – experts in air filtration!

